

# ES0607DC

This model is electrically driven and has a robust and mobile structure. The electric scissor lift system saves energy, ensuring zero emissions and a silent-running. It is ideal for indoor usages.



ZERO EMISSIONS

## STANDARD EQUIPMENTS:

- Automatic pothole protection system
- Crushing protection
- High ground clearance
- Self-locking door on the platform
- Speed limit at maximum height
- Platform load sense system
- Automatic braking system
- Emergency brake release
- Non-marking tyres
- Tilt indicator with alarm
- Warning siren during lowering and dual flashing LED light
- Safety bracket for maintenance operations
- Horn
- Cylinder locking valve
- Emergency stop button
- Emergency lowering
- Traction engine protection
- Anchoring eyebolts
- Onboard diagnostics system
- Hour counter
- Proportional controls
- Fold-down guardrails
- Power to platform
- Maintenance free battery
- Explosion-proof tubing system
- Motion Alarm
- Integrated holes for fork transport
- Charging protection system
- Charging indicator
- Tie-down and lifting points
- One way platform extension deck
- Two-wheel drive
- 2 Wheels Steering
- Manual emergency brake release

## MAIN APPLICATIONS



Maintenance



Plant Service



Construction



Storage/  
Warehouse



Cleaning



Painting/  
Restoration

### ES0607DC

Load capacity	240 kg
Load capacity when extended	100 kg
Max no. Occupants (Indoor/outdoor)	2/1
<b>A</b> Working height	5.6 m
<b>B</b> Platform floor level height	3.6 m
<b>C</b> Overall length	1.44 m
<b>D</b> Overall width	0.76 m
<b>E</b> Overall height (rails up)	1.99 m
<b>F</b> Transport height (rails down)	1.62 m
Platform dimensions (length/width)	1.29x0.7 m
<b>G</b> Platform extension	0.6 m
Ground clearance (stowed)	6 cm
Ground clearance (raised)	1.5 cm
<b>H</b> Wheelbase	1.05 m
Turning radius (inside)	40 cm
Turning radius (outside)	1.55 m
Driving motors	2x24VDC/0.4kW
Lifting motors	24VDC/1.2kW
Travel speed (stowed)	4 km/h
Travel speed (raised)	0,6 km/h
Batteries	24 V/85 Ah AGM batteries maintenance free
Integrated battery charger	24V/15A
Gradeability	25%
Maximum working slope	1,5°/3°
Non-marking tyres	230x80 mm
Weight (CE)	920 kg



Non-marking solid tyres



Safety bracket

**STANDARDS COMPLIANCE:**  
EN 280, ANSI/SAIA A92.20

