









DAB24RT

Articulated boom lifts



STANDARD EQUIPMENT

- · Oscillating front axle
- · Two travel speeds
- · Two-wheel steering
- · Four-wheel drive
- 360° rotation (continuous)
- Proportional controls
- · Thumb rocker steering
- Flashing light
- Non-marking tyres
- Horn
- · Hour counter
- · Harsh environment kits
- · 12V DC Auxiliary power

ENGINE

- · Stage V engine
- Special integrated driveshaft
- · Auto-engine fault shutdown
- · Anti-reverse engine device
- · Anti-restart engine protection
- · Hydraulic oil radiator

BASKET

- Self-levelling
- Rotation +/-90°
- · Schuko power socket 16A/250 V

SAFETY

- Drive enable system
- · Platform load moment indicator
- On-board diagnostics system
- Emergency lowering system
- Tilt indicator with alarm
- · Crushing protection









LOAD CHART 26 25 24 23 22 21 20 19 17 16 15 14 300 kg 13 12 11 10 9 8 7 6 5 4 3 2 1 0 -1 -2 -3 -4 m -3 -2 -1 0 1 2 3 4 5 6 7 8 9 1011 1213 1415 1617 18

		_			
n I	W	НΑ	MG.	\mathbf{a}	NS
- ' /	11.1		1	101	

Platform length	9.83 m
Platform length (transport, basket rotated)	7.67 m
Platform width (tyres)	2.50 m
Platform width (transport)	2.50 m
Platform height	2.89 m
Platform height (transport)	3.00 m
Wheelbase	2.80 m
Tailswing	1.61m
Ground clearance	0.41 m





DAB24RT

Technical data		
Max. working height	24.82 m	
Max. basket height	22.82 m	
Articulation point	9.14 m	
Max. reach	17.00 m	
Turning radius (outside)	3.22 m	
Turning radius (inside)	1.87 m	
Basket width	0.91 m	
Basket length	2.44 m	
Basket rotation	180°	
Jib type	Standard	
Jib length	2.31 m	
Jib Vertical Rotation	135 °	
Below-ground height	4.03 m	
Below-ground reach	9.14 m	
Auxiliary power	12 V DC	
Performance		
Platform max. load capacity	300 kg	
Max. occupants	2	
Max. gradeability (stowed)	45%	
Max. working slope	X-5°/Y-5°	
Max. wind speed	12.5 m/s	
Travel speed (closed config.)	6.0 km/h	
Travel speed (working config.)	1.1 km/h	
Turret rotation (continuous)	360°	
Engine		
Power	Deutz TD2.9 L4/55.4kW	
Diesel tank capacity	135 l	
Hydraulic tank capacity	165 l	
Transmission	Hydrostatic	
Specific features		
Tyres	385/45-28	
Total weight	17,200 kg	

STANDARDS COMPLIANCEE: EN 280, ANSI/SAIA A92.20

The data given in this brochure are provided for information purposes and are subject to change without prior notice.

All images are purely guideline and might not give an exact representation of the product.